



Poly bd® 605E

Safety Data Sheet

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Section 1: Identification

1.1. Product identifier

Product form : Substance
Product Identifier(s) : Poly bd® 605E
CAS-No. : 129288-65-9

1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Elastomers

1.3. Details of the supplier of the safety data sheet

Resin Solutions, LLC
665 Stockton Drive, Suite 100
Exton, PA 19341

For non-emergency product information:
Phone: +1-484-284-8998
Email: product.stewardship@resinsolutions.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (Toll Free USA & Canada) / 703-527-3887 (Multiple languages)
Resin Solutions, LLC: +1-484-284-8989 (Language: English only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Not classified

2.2. Label elements

GHS US labeling

Hazard statements (GHS-US) : **This material has no classified hazards under 29 CFR 1910.1200.**
Precautionary statements (GHS-US) : Precautionary statements not required. Consult the SDS for additional safety information.

2.3. Hazards not otherwise classified

Other hazards which do not result in classification : Contact with hot material - prevent serious burns
The working steams can irritate the eyes as well as the respiratory tract
Repeated exposure may cause skin dryness or cracking.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

2.5. Additional information

Based on conditions common to industrial workplace use of this product : Contact with skin or eyes with hot material may cause serious thermal burns.
Vapors formed when material is processed at high temperatures may be irritating to the eyes and upper respiratory tract.

Section 3: Composition/Information on ingredients

3.1. Substance

Substance type : Polymer
Name : Poly bd® 605E
CAS-No. : 129288-65-9
Chemical name : 1,3-Butadiene, homopolymer, epoxidized, hydroxy-terminated

3.2. Mixture

Not applicable

Section 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Poly bd® 605E

Safety Data Sheet

First-aid measures after skin contact	: Gently wash with plenty of soap and water. If irritation persists, consult a doctor. Heated Material: For serious burns from heated material, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking, tears or redness persist. Heated Material: For serious burns from heated material, get medical attention. In case of contact with the eyes : Rinse immediately with plenty of water for 15 minutes.
First-aid measures after ingestion	: Rinse mouth out with water. If necessary seek medical advice.
4.2. Most important symptoms and effects, both acute and delayed	
Symptoms/effects	: The working steams can irritate the eyes as well as the respiratory tract.
Symptoms/effects after skin contact	: Contact with hot material - prevent serious burns. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Contact with hot material - prevent serious burns.
4.3. Indication of any immediate medical attention and special treatment needed	
Treat symptomatically.	

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray or fog. Carbon dioxide. Foam. Dry chemical. Dry powder. Sand.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the chemical

Fire hazard	: Heat from fire can generate flammable vapor. When mixed with air and exposed to ignition source, can burn in open air or explode if confined.
Explosion hazard	: Flammable or explosive vapor/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂). Toxic fumes. 1,3-butadiene. Hydrocarbons.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Avoid direct personal contact with liquid even after fire is out to prevent potentially serious burns. Use water spray or fog for cooling exposed containers. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.
Other information	: Fires are typically very smoky.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures for non-emergency personnel	: Ensure adequate ventilation. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures for emergency responders	: No additional requirement.

6.2. Methods and material for containment and cleaning up

For containment	: Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite. Keep recovered product for subsequent disposal.
Methods for cleaning up	: Wash away residue with large amounts of water. Gather the product and place it in a spare container that has been suitably labeled.

6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

Section 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with elevated temperature or molten product to prevent burns. Wear personal protective equipment. Use only non-sparking tools. Eliminate all ignition sources if safe to do so. Steam drum heaters are recommended. If heating is necessary for drummed product, loosen or remove bung or lid before warming/heating product to avoid overpressurization in the drum. If frozen, thaw and mix thoroughly before use.
-------------------------------	---

Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Containers which are opened should be properly resealed and kept upright to prevent leakage.
--------------------	--

Poly bd® 605E

Safety Data Sheet

Storage conditions	: Keep container tightly closed. Store in a dry, cool area. Purge open drums with nitrogen before resealing. Viscosity may increase over time. Keep away from sources of ignition.
Incompatible materials	: Strong oxidizing agents. Strong reducing agents. Strong acids.
Storage temperature	: 10 – 32 °C

Section 8: Exposure controls/personal protection

8.1. Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV, or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

None

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Safety shower. Eye fountain.
Hand protection	: Impermeable protective gloves. Do not use natural rubber gloves. Product used with solvents : wear thick (> 0.5 mm) nitrile gloves. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility, etc.) is noticed.
Eye protection	: Safety glasses with side shields.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Color	: clear.
Odor	: Aromatic.
Odor threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: > 200 °C
Flash point	: > 110 °C (SETA)
Auto-ignition temperature	: No data available
Decomposition temperature	: > 350 °C
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.01
Solubility	: Water: practically insoluble
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 5000 mPa·s (30 °C)
Explosion limits	: No data available

9.2. Other information

No additional information available

Section 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Direct sunlight. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents. Strong acids.

Poly bd® 605E

Safety Data Sheet

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Ingestion. Skin and eye contact.

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified
Slight skin irritant (rabbit)

Serious eye damage/irritation : Not classified
Slight eye irritant (rabbit)

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : The working steams can irritate the eyes as well as the respiratory tract.

Section 12: Ecological information

12.1. Toxicity

Ecology - general : Do not flush into surface water or sewer system. The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Poly bd® 605E

Safety Data Sheet

Section 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Transfer to a safe disposal area in accordance with federal, state, and local regulations.
- Product/Packaging disposal recommendations : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 14: Transport information

US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Not regulated by US DOT

Transport by sea (IMDG)

Not regulated by IMDG

Air transport (IATA)

Not regulated by IATA

Section 15: Regulatory information

15.1. US Federal regulations

EPA TSCA Status

All components of this product are listed or exempt from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) Active inventory. This product has no special requirements under TSCA, such as significant new use rules (SNUR), consent orders, test rules, or sections 4, 5, 6, 8(a), 8(d), 12(b) requirements.

SARA Section 313 Supplier Notification

This product contains no toxic chemicals in excess of the applicable de minimis concentration that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA Section 311/312 Hazard Classes : Not applicable

Export Control Statement: This product is controlled in certain EU member countries under Export Control Classification Number 1C111. The product may not be exported from the EU without a license from the relevant authority(ies). Shipments of this product from the U.S. are not export controlled (EAR99). Diversion contrary to law is prohibited.

15.2. International regulations

CANADA

Poly bd® 605E (129288-65-9)

WHMIS Classification : This product is not regulated according to WHMIS 2015 classification criteria

National inventories

Poly bd® 605E (129288-65-9)

Listed on the Canadian Non-Domestic Substances List (NDSL)
Listed on or exempt from listing on the China Inventory of Existing Chemical Substances (IECSC)

EINECS (European Inventory of Existing Commercial Chemical Substances) : All components are listed or exempted

15.3. US State regulations

This product may contain California Proposition 65 substances at concentration levels below those required to be classified as hazardous by OSHA's Hazard Communication Standard (29 CFR 1910.1200). Contact Resin Solutions, LLC if you need specific information regarding status of this product with regard to California Proposition 65.

Section 16: Other information


Other information : Unless agreed to in a separate written agreement with the Customer, Resin Solutions, LLC makes no representations and disclaims all warranties, express or implied, with respect to biocompatibility and/or the suitability of this product for medical device applications including : (i) implantable devices intended for human or animal body, (ii) devices intended to be used in contact with internal body fluids, and (iii) devices intended to be used in contact with internal body tissues. If the Customer intends to use this product for any such application, it must first contact Resin Solutions, LLC and establish agreed terms and conditions for such use.

Poly bd® 605E

Safety Data Sheet

NFPA (National Fire Protection Association)

NFPA health hazard : 1
NFPA fire hazard : 1
NFPA reactivity : 1



Hazard System Rating

Health : 1
Flammability : 1
Physical Hazard : 1
Personal protection : See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f). The label shown may include supplemental information in addition to required elements.

Poly bd® 605E

Resin Solutions, LLC
665 Stockton Drive, Suite 100
Exton, PA 19341 USA
Tel. +1-484-284-8989

This material has no classified hazards under 29 CFR 1910.1200.

Precautionary statements not required. Consult the SDS for additional safety information.

US SDS Version: 4.0

Issue date: November 6, 2023

SDS ID: POLY_BD_605E
SDS REFERENCE NUMBER: 3001T

SDS Template - Resin Solutions LLC US Version 1.0

The information contained in this Safety Data Sheet (SDS) is believed by Resin Solutions, LLC to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither Resin Solutions, LLC nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.